



# NC-100/200™

Portable Traffic Analyzer

## Overview

The NC-100/200 is a portable traffic analyzer designed to provide accurate count, speed, and classification data. The sensor is placed directly in the traffic lane to measure data, and can be installed and removed quickly and easily. The NC-100 model provides count only, while the NC-200 model provides count, speed and classification of vehicles.

The sensor combines accuracy and portability, monitoring traffic flow conditions right where you need them. Whether you are surveying traffic on a local roadway, bridge, parking garage, construction area, or in and out of local points of interest, the NC-100/200 provides key data necessary for effective traffic analysis.

The NC-100/200 utilizes Vehicle Magnetic Imaging (VMI) technology to detect vehicle count, speed and classification. The data is easily exported to Highway Data Management (HDM) software, where it can be presented in the form of reports, charts and graphs.

## Benefits

- ▶ Portable sensor detects vehicle count, speed and classification
- ▶ Can be installed and removed in minutes
- ▶ Less noticeable to traffic, which results in more accurate information

## Applications

- ▶ Traffic studies
- ▶ Parking lots, garages, and shopping centers
- ▶ Temporary studies for roadway planning
- ▶ Construction zones
- ▶ Airports, stadiums, and casinos
- ▶ Military bases and border crossings
- ▶ Parks or recreational areas
- ▶ Police departments (for speed studies)
- ▶ Stop signs, traffic lights, or posted speeds



# NC-100/200™

## Portable Traffic Analyzer

### Features

- ▶ Accurately measures vehicle count, speed, and classification
- ▶ Categorizes traffic into bins or by individual vehicle
- ▶ 15 speed bins and 13 length classification bins (configurable)
- ▶ Durable extruded aluminum housing
- ▶ Long life, rechargeable, Lithium-ion battery
- ▶ Connects to any computer for easy data retrieval
- ▶ Easy to use software for viewing data
- ▶ Software allows you to change your parameters after the study



### Key Specifications

Housing Material	Extruded/anodized aluminum
Ultimate Bearing Strength	88,000 psi (607 Mpa)
Dimensions	7.125 x 4.625 x 0.5 inches (181 x 118 x 12.7 millimeters)
Weight	1.3 pounds (0.59 kilograms)
Operating Temperature	-4°F to +140°F (-20°C to +60°C)
Sensor	GMR magnetic chip for Vehicle Magnetic Imaging
Memory	Micro Serial Flash: 3MB
Battery/Power	Lithium-ion rechargeable (up to 21 days before recharge)
Computed Values	Imperial or Metric
*Capacity	Up to 300,000 vehicles or 21 days per study, whichever occurs first
*Length Classification (% of Volume)	13 bins (user selectable length range)
*Speed Class (% of Volume)	15 bins (user selectable speed range)
Vehicle Detection	Detects vehicles between 8 and 120 mph (13 to 193 kph)

\*Applies to model NC-200

Specifications subject to change without notice.



Quixote Transportation Technologies, Inc.  
P.O. Box 260  
Mt. Braddock, Pennsylvania 15465  
Toll Free: 800-325-7226  
Phone: 314-569-1002  
Fax: 314-569-3567  
www.qttinc.com

Distributed by:



PWS Ireland maintains the following certifications:  
BS EN ISO 14001: 2004  
BS EN ISO 9001: 2000  
OHSAS 18001: 1999